



AT-10™ Air Tool Oil

Product Data Sheet

General Information

- Recommended for piston and rotary type air tools
- Lubricates, cleans & protects
- Lubrication technology based on tribologic methods that improve lubricity & load-carrying capacity
- Contains Muscle MT-10™ Metal Treatment technology for increased lubricity & boundary film lubrication

Typical Applications

- Impact & ratchet wrenches
- Nailers & staplers
- Hammers
- Sanders, grinders & polishers
- Shears
- Drill & screw drivers
- Chisels
- Saws
- Paving breakers
- Riveters
- Tampers
- Rock drills
- And any other piston or rotary type air tool

Key Features & Benefits

- Lubricates, cleans & protects
- Stops & inhibits rust
- Repels air line moisture & water spray
- Removes gummy deposits
- Improves tool performance
- Extends tool life
- Reduces maintenance & replacement costs

Availability

- 4-oz. & 16-oz. bottles (118 & 474 ml)
- 1 & 5 U.S. gallon containers (3.8 & 18.9 L)
- 55 U.S. gallon drum (208 L)

Directions for Use

Shake product lightly. Use in accordance with air tool manufacturer's instructions. Tools may need lubricated daily, or several times a day, depending on the frequency of tool use.

NOTE: All petroleum oils have a tendency to cause **natural rubber** o-rings to swell. Before using **AT-10™**, please check with your equipment manufacturer to make sure your air tools utilize **quality non-rubber (i.e. neoprene) o-rings**.

Typical Properties

Boiling Point	> 450°F (232°C)
Autoignition Temperature	469°F (243°C)
Flash Point	282°F (139°C) D93
Specific Gravity @ 60°F, g/cm ³	0.945
API Gravity @ 60°F	18.2
Density	7.888 lbs per US gal
Vapor Pressure	< 0.810 PSI
Viscosity @ 40°C, cSt	25.05
Viscosity @ 100°C, cSt	3.90
Pour Point	< - 50°F (- 45.6°C)
Cloud Point	14.7°F (- 9.8°C)
Odor	Mild petroleum, hint of cinnamon
Color & Appearance	Red low viscosity liquid
Solubility in Water	Insoluble

Copyright 1986-2012 Muscle Products Corp.
Rev. 9/2012

